

Cleaner and Degreaser

Revision: 7/04/2015

Page 1 from 1

Technical data

| | |
|----------------------------------|--------------------------|
| Basis | 100% hydrocarbon solvent |
| Consistency | Liquid |
| Density | Ca. 0,75 g/ml |
| Acidity level (text) | Neutral |
| Solubility in water | Not soluble |
| Volatile Organic Compounds (VOC) | 97 % |
| Application temperature | 5 °C → 30 °C |

(*) these values may vary depending on environmental factors such as temperature, moisture, and type of substrates.

Product description

Cleaner and Degreaser is a powerful quick-drying cleaner and degreaser for various maintenance and assembly jobs.

Properties

- Cleans and degreases
- Leaves no residue
- Fast drying
- Aerosol can be used in any angle (360°)

Applications

- Suitable for cleaning and degreasing mechanical parts. Also suitable for the preparation of surfaces
- for the application of sealants or adhesives. For the removal of uncured excess MS, PU or silicone
- sealants, tar residue, grease, wax,... Can be used on most surfaces (metal, plastics, PVC,...) and leaves no residue.

Packaging

Colour: transparent

Packaging: 400 ml aerosol

Shelf life

3 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

Substrates

Nature: clean, free of dust and grease.

All types of metals and plastics.

Application method

Application method: Shake can well before use. Spray at a distance of appr. 20 cm of the object. Apply as required. After applying rub the surface dry with a clean towel. Always rub in one direction. Test for adverse effects on the surface in advance.

Health- and Safety Recommendations

Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water.

Remarks

- Due to the wide variety of possible plastics and paints and to avoid damage to the surface, a preliminary compatibility test is recommended.

Liability

The content of this technical data sheet is the result of tests, monitoring and experience. She is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions beyond our control, no liability under this publication are accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.