

Surface Cleaner

Revision: 6/03/2018

Page 1 from 1

Technical data

Basis	Solvent mixture
Consistency	Fluid
Density	0,73 g/ml
Flashpoint	< -10 °C
Boiling point	107-137°C
Kinematic viscosity (25°C)	0.6 mm ² /s
Vapour pressure (20°C)	Ca. 30-40 hPa
Application temperature	5 °C → 25 °C

(*) these values may vary depending on environmental factors such as temperature, moisture, and type of substrates.

Product description

Surface Cleaner is a solvent cleaner designed to remove uncured MS polymer based sealant remains. Surface Cleaner also removes dirt residues.

Properties

- Very easy to apply
- Fast drying
- Excellent cleaning properties
- Suitable for most plastics and metals.

Applications

- Removal of adhesives, sealants, tapes, stickers, chewing gum, non cured PU foam, etc.
- Cleaning of non-porous surfaces.

Packaging

Colour: colorless

Packaging: 500 ml alu tin

Shelf life

2 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C.

Substrates

Substrates: all usual building substrates

Nature: clean, dry, dust-free.

Surface preparation: No pretreatment required.

It is recommended to perform a preliminary compatibility test on any surface.

Application method

Application method: Apply Surface Cleaner with a cloth soaked in product. Always work with a clean cloth to avoid contamination of the surface. Replace if necessary. Always wipe in one direction. After cleaning the surface let dry sufficiently before applying the kit. Remove cured sealant with Sealant Remover and spatula or stiff brush.

Health- and Safety Recommendations

Take the usual labour hygiene into account. Consult label for more information.

Remarks

- Due to the wide variety of possible plastics and paints and to avoid damage to the surface, a preliminary compatibility test is recommended.

Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.